



Sustainable Production of Dimethyl Carbonate and Ethylene Glycol Via a Systematic Process Design Framework

Pudi, A.; Koyyalamudi, B. B.; Martínez, P. D. ; Bertran, M. O.; Jhamb, S.

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):

Pudi, A., Koyyalamudi, B. B., Martínez, P. D., Bertran, M. O., & Jhamb, S. (2017). *Sustainable Production of Dimethyl Carbonate and Ethylene Glycol Via a Systematic Process Design Framework*. Abstract from 2017 AIChE Annual Meeting , Minneapolis, Minnesota, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

(189i) Sustainable Production of Dimethyl Carbonate and Ethylene Glycol Via a Systematic Process Design Framework



Conference: AIChE Annual Meeting

Year: 2017

Proceeding: 2017 AIChE Annual Meeting

Group: Computing and Systems Technology Division

Session: Interactive Session: Systems and Process Design

Time: Monday, October 30, 2017 - 3:15pm-4:45pm

Authors:

Pudi, A., Technical University of Denmark

Koyyalamudi, B. B., Technical University of Denmark

Martínez, P. D., Technical University of Denmark

Bertran, M. O., Technical University of Denmark

Jhamb, S., Technical University of Denmark

In the past several decades, there has been a growing awareness and an increasing concern in the public

AIChE websites use cookies to offer you a better browsing experience and analyze site traffic. By using our websites, you consent to our use of cookies. [More info](#)

Got it

As a potential strategy to reduce carbon dioxide emissions into the atmosphere, CO₂ utilization processes have gained much attention in recent times as means to produce fine chemicals. Dimethyl carbonate (DMC) is one such product that can be synthesized by utilizing CO₂.

Dimethyl carbonate is a non-toxic, readily biodegradable chemical that exhibits high reactivity [1]. DMC received its VOC exemption under the Clean Air Act on January 13, 2009 by the US EPA. While the traditional production from phosgene and methanol uses toxic and hazardous chemicals, DMC can now be produced via the transesterification of ethylene carbonate (EC) and methanol. EC is obtained from reacting ethylene oxide (EO) with CO₂. Ethylene glycol (EG) is a valuable product that is coproduced in this process.

A sustainable process is developed to produce DMC and EG using a systematic framework [2]—a twelve-step hierarchical decomposition method. Using this approach, a plant with an annual production capacity of about 100,000 tonnes of DMC is designed. EO, CO₂, and methanol are the raw materials. EO and CO₂ are first reacted at 120 °C and 20 bar to form EC. A flash is used to separate EC from impurities and unreacted components. The EC stream is sent into the second reactor to react with methanol at 60 °C and atmospheric pressure to produce DMC and EG. The outlet of this reactor contains DMC-methanol and EG-EC azeotropes that are separated in a distillation column at atmospheric pressure. The overhead stream of DMC and methanol is separated in a high-pressure distillation column at 40 bar while the bottoms stream of EC and EG are separated using a membrane. Once the sizing and costing are done, a base case design is obtained.

An economic analysis is performed on the base case design to identify process hotspots that are translated into design targets for process integration and optimization. The resulting process is then put through sustainability analysis [3] and life cycle assessment [4] to refine it further with respect to environmental impact. In this project, PRO/II is used as the simulation tool. The final objective is to obtain a more sustainable process design that is also able to achieve a negative net CO₂ emission.

[1] P. Tundo and M. Selva, “The Chemistry of Dimethyl Carbonate”. *Acc Chem Res*, 2002, vol. 35 (9), pp 706–716.

[2] D. K. Babi, "Teaching Sustainable Process Design using 12 systematic Computer Aided Tasks". *Computer Aided Chemical Engineering*, 2015, vol. 37, pp. 173-178.

[3] A. Carvalho, H. A. Matos, and R. Gani, “SustainPro—A tool for systematic process analysis, generation and evaluation of sustainable design alternatives”. *Comput. Chem. Eng.* Mar. 2013, vol. 50, pp. 8–27.

[4] S. Kalakul, P. Malakul, K. Siemanond, and R. Gani, “Integration of life cycle assessment software with tools for economic and sustainability analyses and process simulation for sustainable process design”. *J. Clean. Prod.* May 2014, vol. 71, pp. 98–109.

Topics: [Process Design & Development](#) | [Sustainable Engineering](#)

Translate this page

AIChE websites use cookies to offer you a better browsing experience and analyze site traffic. By using our websites, you consent to our use of cookies. [More info](#)

Got it

LinkedIn

Twitter

Facebook

YouTube

Flickr

Slide Share

About

Join AIChE

Global

Contact

Advertise

Ethical Guidelines

Press

Privacy & Security

Code of Ethics

Sitemap

Copyright © American Institute of Chemical Engineers. All rights reserved.